

Motor pump	LOMBARDINI on Barrow	Pump	ROVATTI
-------------------	-----------------------------	-------------	----------------

STANDARD EQUIPMENT:

- Air-cooled LOMBARDINI engine, complete with engine liquids and fuel tank.
- Mounted on two pneumatic wheel barrow.
- Flanged Centrifugal PUMP

PULL START

MODEL	ENGINE	PUMP	MAX POWER HP/KW - STANDARDS OF REFERENCE	R.P.M. n.1'	Q l/min.	H mt.	SUCT. Ø DEL.	STANDARD FRAMES TANK		
L01R608	15LD350	FL416F-CA	7/5	3000	200	33	65	SLR2		
	SINGLE CYLINDER 349 cc		CE 1997/68 STEP II		350	31	40	4,3 LITER		
L01R607	15LD350	FL320G-CA	8/6	3000	100	46	50	SLR2		
	SINGLE CYLINDER 349 cc		CE 1997/68 STEP II		200	44	32	4,3 LITER		
L05R610	3LD510	FL420/2H-CA	12/9	2600	200	58	50	SLR2		
	SINGLE CYLINDER 510 cc		UTI		400	48	40	5,3 LITER		
L03R611	15LD440	FL516FG-CA	11/8	3000	300	33	65	SLR2		
	SINGLE CYLINDER 442 cc		CE 1997/68 STEP II		900	29	50	5 LITER		
L04R668	15LD500	FL612G-CA	12/9	3000	800	25	80	SLR2		
	SINGLE CYLINDER 505 cc		CE 1997/68 STEP II		1400	20	65	5 LITER		
L04R610	15LD500	FL420/2H-CA	12/9	2600	200	58	50	SLR2		
	SINGLE CYLINDER 505 cc		CE 1997/68 STEP II		400	48	40	5 LITER		
L06R615	4LD820	FL420/3E-CA	18/13	2600	200	93	50	SLR2		
	SINGLE CYLINDER 817 cc		UTI		350	82	40	5 LITER		
L06R613	4LD820	FL616E-CA	18/13	2600	1000	29	80	SLR2		
	SINGLE CYLINDER 817 cc		UTI		1400	26	65	5 LITER		

Motor pump	LOMBARDINI on Barrow	Pump	ROVATTI
-------------------	-----------------------------	-------------	----------------

STANDARD EQUIPMENT:

- Air-cooled LOMBARDINI engine, complete with engine liquids and fuel tank.
- Mounted on two pneumatic wheel barrow.
- Electric start with key block and battery
- Flanged Centrifugal PUMP

ELECTRIC START

MODEL	ENGINE	PUMP	MAX POWER HP/KW - STANDARDS OF REFERENCE	R.P.M. n.1'	Q l/min.	H mt.	SUCT. Ø DEL.	STANDARD FRAMES TANK		
L21R608	15LD350	FL416F-CA	7/5	3000	200	33	65	SLR2		
	SINGLE CYLINDER 349 cc		CE 1997/68 STEP II		350	31	40	4,3 LITER		
L21R607	15LD350	FL320G-CA	8/6	3000	100	46	50	SLR2		
	SINGLE CYLINDER 349 cc		CE 1997/68 STEP II		200	44	32	4,3 LITER		
L27R610	3LD510	FL420/2H-CA	12/9	2600	200	58	50	SLR2		
	SINGLE CYLINDER 510 cc		UTI		400	48	40	5,3 LITER		
L23R611	15LD440	FL516FG-CA	11/8	3000	300	33	65	SLR2		
	SINGLE CYLINDER 442 cc		CE 1997/68 STEP II		900	29	50	5 LITER		
L24R668	15LD500	FL612G-CA	12/9	3000	800	25	80	SLR2		
	SINGLE CYLINDER 505 cc		CE 1997/68 STEP II		1400	20	65	5 LITER		
L24R610	15LD500	FL420/2H-CA	12/9	2600	200	58	50	SLR2		
	SINGLE CYLINDER 505 cc		CE 1997/68 STEP II		400	48	40	5 LITER		
L25R670	25LD330/2	FL520G-CA	16/12	3000	200	48	65	SLR2		
	2 CYLINDER 654 cc		CE 1997/68 STEP II		800	42	50	4 LITER		
L28R615	4LD820	FL420/3E-CA	18/13	2600	200	93	50	SLR2		
	SINGLE CYLINDER 817 cc		UTI		350	82	40	5 LITER		
L28R613	4LD820	FL616E-CA	18/13	2600	1000	29	80	SLR2		
	SINGLE CYLINDER 817 cc		UTI		1400	26	65	5 LITER		
L26R612	25LD425/2	FL524I-CA	19/14	3000	200	59	65	SLR2		
	2 CYLINDER 851 cc		CE 1997/68 STEP II		600	53	50	4 LITER		

Motor pump	LOMBARDINI - PERKINS, on trolley	Pump	ROVATTI
-------------------	---	-------------	----------------

STANDARD EQUIPMENT:

- 2, 3 cylinder air-cooled engine, complete with engine liquids and fuel tank.
- Mounted on two pneumatic wheels trolley, with builtin tank
- Flanged Centrifugal PUMP
- Electric start with key block and battery
- PERKINS: ELCOS CEM 250/00 control panel with electric system, engine control device, pressure gauge, pressure switch, 24 hour timer.
- Battery

MODEL	ENGINE	PUMP	MAX POWER HP/KW - STANDARDS OF REFERENCE	R.P.M. n.1'	Q l/min.	H mt.	SUCT. Ø DEL.	STANDARD FRAMES TANK		
L26R612	25LD425/2	FL524I-CA	19/14	3000	200	59	65	S101		
	2 CYLINDER 851 cc		CE 1997/68 STEP II		600	53	50	60 LITER		
L40R660	12LD477/2	FL526GH-CA	23/17	2600	200	55	65	S101		
	2 CYLINDER 954 cc		CE 1997/68 STEP II		600	52	50	60 LITER		
L40R618	12LD477/2	FL619AE-CA	23/17	2600	1000	38	80	S101		
	2 CYLINDER 954 cc		CE 1997/68 STEP II		1400	33	65	60 LITER		
L44R664	9LD625/2	FL626G-F1	26/19	2600	800	57	80	S101		
	2 CYLINDER 1248 cc		CE 1997/68 STEP II		1300	51	65	60 LITER		
L44R601	9LD625/2	FL526/2I-F1	26/19	2600	200	89	65	S101		
	2 CYLINDER 1248 cc		CE 1997/68 STEP II		400	87	50	60 LITER		
L44R604	9LD625/2	FL822BH-F1	26/19	2600	1000	40	100	S101		
	2 CYLINDER 1248 cc		CE 1997/68 STEP II		1800	33	80	60 LITER		
L71R601	11LD626/3	FL526/2F-F2	42/31	2600	200	111	65	S101		
	3 CYLINDER 1870 cc		CE 1997/68 STEP II		600	101	50	60 LITER		
L71R675	11LD626/3	FL626/2I-F2	42/31	2600	800	85	80	S101		
	3 CYLINDER 1870 cc		CE 1997/68 STEP II		1000	81	65	60 LITER		
K07R735	403D-15 IOPU	F43K65/4E	33/24	2000	200	120	65	S102		
	3 CYLINDER 1496 cc		TIER III STAGE 3A		450	107	50	60 LITER		
K08R709	404D-22 IOPU	F43K80/3E	50/37	2000	400	96	80	S103		
	4 CYLINDER 2200 cc		TIER III STAGE 3A		800	88	65	60 LITER		
K08R715	404D-22 IOPU	F43K80/4H	50/37	2000	500	108	80	S103		
	4 CYLINDER 2200 cc		TIER III STAGE 3A		800	100	65	60 LITER		
K08R706	404D-22 IOPU	F43K100/2M	50/37	1800	800	60	100	S103		
	4 CYLINDER 2200 cc		TIER III STAGE 3A		1200	56	80	60 LITER		