



Pompe carellate monogiranti Single stage pumps trailer-mounted

Tipo Pompa Type Pump	Girante Impeller		Bocche Pompa Ports Pump		Giri presa forza R.P.M. PTO	Rapporto Ratio	Giri Pompa /1' R.P.M. Pump	Prestazioni Performance			Potenza Trattore Power Tractor HP
	ø mm.	apertura opening mm.	DNa	DNm				Portata Delivery l/1'	Prevalenza High head H mt.	Cv ass.	
CA80-515A3	330	9	100 mm.	80 mm.	540	1 : 5,15	2600	900 1200 1600 2000 2500	112 109 105 96 83	58 66 74 83 90	100
CA80-515B3	320	9	100 mm.	80 mm.	540	1 : 5,15	2600	900 1200 1600 2000 2500	106 103 98 89 76	54 61 69 77 85	100
CA80-515C3	310	9	100 mm.	80 mm.	540	1 : 5,15	2600	900 1200 1600 2000 2500	100 97 92 83 70	51 57 65 72 79	85
CA80-315A3	330	9	100 mm.	80 mm.	850	1 : 3,15	2600	900 1200 1600 2000 2500	112 109 105 86 83	58 66 74 83 90	90
CA80-315B3	320	9	100 mm.	80 mm.	850	1 : 3,15	2600	900 1200 1600 2000 2500	106 103 98 89 76	54 61 69 77 85	100
CA80-315C3	310	9	100 mm.	80 mm.	850	1 : 3,15	2600	900 1200 1600 2000 2500	100 97 92 83 70	51 57 65 72 79	85
CA80-538A4	249	18	100 mm.	80 mm.	540	1 : 5,38	2900	1500 2000 2500 3000 3300	100 98 95 90 85	63 68 77 86 94	110
CA80-538B4	240	18	100 mm.	80 mm.	540	1 : 5,38	2900	1500 2000 2500 3000 3300	86 84,3 81,7 77,4 73,1	50,4 54,4 61,6 68,8 75,2	90
CA80-538C4	230	18	100 mm.	80 mm.	540	1 : 5,38	2900	1500 2000 2500 3000 3300	72,5 71 68,8 65,2 61,5	39 42,2 48 54 59	70
CA80-340A4	249	18	100 mm.	80 mm.	850	1 : 3,40	2900	1500 2000 2500 3000 3300	100 98 95 90 85	63 68 77 86 94	110
CA80-340B4	240	18	100 mm.	80 mm.	850	1 : 3,40	2900	1500 2000 2500 3000 3300	86 84,3 81,7 77,4 73,1	50,4 54,4 61,6 68,8 75,2	80
CA80-340C4	230	18	100 mm.	80 mm.	850	1 : 3,40	2900	1500 2000 2500 3000 3300	72,5 71 68,8 65,2 61,5	39 42,2 48 54 59	70
CA150-430	210	32	150 mm.	150 mm.	540	1 : 4,30	2300	2800 3000 3200 3400 4000 4500	27 24 22,5 21 19 15,6	22,4 22,7 23 23,5 24 24,5	35
CA200-314L	220	30	200 mm.	200 mm.	510	1 : 3,14	1600	4000 5000 6000 7000 9000	14,2 13,6 12,8 11,5 7,5	22 24 26 27,2 28	35
CA200-314E	210	30	200 mm.	200 mm.	510	1 : 3,14	1600	4000 5000 6000 8000 10000	26,2 25,7 25,1 22,7 17,7	40 44 48 53,7 55	65
CA250-314	240	40	250 mm.	250 mm.	510	1 : 3,14	1600	7000 9000 10000 11000 15000 17000	17,7 17,5 17,3 17 12,2 7,5	42 48 50 52,5 52 45	65