




**Pompe carellate monogiranti**  
**Single stage pumps**  
**trailer-mounted**



Serie  
Series

**CA**

Tipo Pompa Type Pump	Girante Impeller		Bocche Pompa Ports Pump		Giri presa forza R.P.M. PTO	Rapporto Ratio	Giri Pompa /1' R.P.M. Pump	Prestazioni Performance			Potenza Trattore Power Tractor HP
	ø mm.	apertura opening mm.	DNa	DNm				Portata Delivery l/1'	Prevalenza High head H mt.	Cv ass.	
<b>CA2-7907</b>	180	7	2"	2"	540	1 : 7,90	4000	230 400 600 800 1000	79 75 70 65 57	8 10,1 12,4 14,2 16	20
<b>CA2-79035</b>	180	3,5	2"	2"	540	1 : 7,90	4000	175 250 320 350 420	74 69 64 61 45	9,6 8,2 8,6 9,2 9,6	15
<b>CA50-738A1</b>	174	10	65 mm.	50 mm.	542	1 : 7,38	4000	500 600 700 800 900 1000	72,7 71,4 69,5 67,2 65 62,2	15,7 17,2 18,4 19,5 20,7 21,7	30
<b>CA50-738B1</b>	169	10	65 mm.	50 mm.	542	1 : 7,38	4000	500 600 700 800 900 1000	63 61,7 60 57 54,4 51,4	12,9 14,1 15,2 16,3 17,2 18	25
<b>CA50-627A1</b>	174	10	65 mm.	50 mm.	638	1 : 6,27	4000	500 600 700 800 900 1000	72,7 71,4 69,5 67,2 65 62,2	15,7 17,2 18,4 19,5 20,7 21,7	30
<b>CA50-627B1</b>	169	10	65 mm.	50 mm.	638	1 : 6,27	4000	500 600 700 800 900 1000	63 61,7 60 57 54,4 51,4	12,9 14,1 15,2 16,3 17,2 18	25
<b>CA50-738A2</b>	210	6	65 mm.	50 mm.	542	1 : 7,38	4000	500 600 700 800 900	99,7 96,8 95,9 93,4 92,6	26,8 28,4 30,0 31,2 32,0	40
<b>CA50-738B2</b>	200	6	65 mm.	50 mm.	542	1 : 7,38	4000	500 600 700 800 900	85,7 83,6 81,5 77,9 73,7	22 23,4 24,8 25,9 27,3	35
<b>CA50-738C2</b>	195	6	65 mm.	50 mm.	542	1 : 7,38	4000	500 600 700 800 900	79,3 77 74,5 71 66,7	19,9 21,2 22,5 23,5 24,7	30
<b>CA50-738D2</b>	190	6	65 mm.	50 mm.	542	1 : 7,38	4000	500 600 700 800 900	74,1 71,3 68,7 65 60,7	18 19,3 20,5 21,4 22,5	30
<b>CA50-627A2</b>	210	6	65 mm.	50 mm.	638	1 : 6,27	4000	500 600 700 800 900	99,7 96,8 95,9 93,4 92,6	26,8 28,4 30 31,2 32	40
<b>CA50-627B2</b>	200	6	65 mm.	50 mm.	638	1 : 6,27	4000	500 600 700 800 900	85,7 83,6 81,5 77,9 73,7	22 23,4 24,8 25,9 27,3	35